

acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: VITROBRAZE 2106[®]

• Material Safety Data Sheet - no.: IB113

- Relevant identified uses of the substance or mixture and uses advised against Not applicable
- Application of the substance / the preparation Brazing foil
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

VACUUMSCHMELZE GmbH & Co.KG

Grüner Weg 37 D-63450 Hanau

datasheet@vacuumschmelze.com

• Information department: Environmental Protection Department

• Emergency telephone number: Tel. no.: (**49) 6181/38-0 Emergency tel. no.: via (**49) 6181/38-0

2 Hazards identification

Classification (substance or mixture)

Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006.

For articles there is no obligation to classify acc. to CLP -Regulation.

GHS label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

Additional VAC information:

In the case of dust-producing processing, we recommend observance of the following warnings:

Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapours/spray.

In case of inadequate ventilation wear respiratory protection.

Use personal protective equipment as required.

Avoid release to the environment.

Do no eat, drink or smoke when using this product.

Get medical advice/attention if you feel unwell.

Other hazards

Danger of accident!

Always wear protective clothing, protective glasses and safety gloves when handling the bands.

- The bands have sharp edges. There is a danger of (serious) injury from cuts.

- The bands can split and cause (serious) cuts when bent excessively
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization:
- Description: Brazing foil

(Contd. on page 2)



acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

Trade name: VITROBRAZE 2106®

(Contd. of page 1)

Dangerous components:

The classifications given below reflect the classification of each <u>pure substance</u> respectively and are intended for information only

CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-00-7	nickel	☐ T R48/23; X Xn R40; Xi R43 Carc. Cat. 3 ♦ H351; H372; ♦ H317	44%
CAS: 7439-89-6 EINECS: 231-096-4	iron		~ 35%
CAS: 7440-47-3 EINECS: 231-157-5	chromium		~ 11%
CAS: 7440-21-3 EINECS: 231-130-8	silicon	F R11	6%
CAS: 7439-98-7 EINECS: 231-107-2	molybdenum		~ 2%
CAS: 7440-50-8 EINECS: 231-159-6	copper		~ 1%

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

Description of first aid measures

After inhalation:

If metal vapours or solid dusts have been inhaled: Get the affected person out in the fresh air and call a doctor.

After skin contact:

Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

After eye contact:

Foreign bodies must be removed, consult a doctor if necessary.

Beware of metal splinters - Consult a doctor immediately.

- After swallowing: Consult a doctor if the symptoms persist.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- Extinguishing media
- Suitable extinguishing agents:

Non-combustible.

Extinguishing agents must be adapted to the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: Wear self-contained respiatory protective device.

6 Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

- Personal precautions, protective equipment and emergency procedures No special measures required.
- Environmental precautions: No special measures required.
- Methods and material for containment and cleaning up: No special measures required.
- Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)



acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

Trade name: VITROBRAZE 2106®

(Contd. of page 2)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- Precautions for safe handling

Danger of accident!

Always wear protective clothing, protective glasses and safety gloves when handling the bands. - The bands have sharp edges. There is a danger of (serious) injury from cuts.

- The bands can split and cause (serious) cuts when bent excessively.

The appropriate industrial and environmental safety measures must be taken for processing steps which cause dust or fumer (see also section 8):

No more safety precautions are necessary in the delivered form.

The appropriate industrial and environmental safety measures

must be taken for processing steps which cause dust

(see also section 8):

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in dry conditions and in the dark.
- Storage class: Not applicable
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:

Provide a suitable suction with filter and good ventilation of the working area for all processing steps.

Suitable breathing apparatus must be used (see personal safety equipment) for repair and maintenance work on suction systems, especially when changing the filters.

Control parameters

 Components 	with limit values that require monitoring at the workplace:	
7440-02-0 nickel		
EL (Canada)	0.05 mg/m ³	
	as Ni; ACIGH A1, IARC 1	
EV (Canada)	1* 0.2** 0.1*** mg/m³	
	inh.;*metal;**insol. compds.;***soluble compds.	
PEL (USA)	1 mg/m³	
REL (USA)	0.01 ⁵ mg/m³	
	as Ni; See Pocket Guide App. A	
TLV (USA)	1.5* 0.2** 0.1*** mg/m³	
	inhal.fraction;*elemental;**insol.,***sol.compds.	
7439-89-6 iron		
EV (Canada)	1* 5** mg/m³	
. ,	as iron;*salts, water-soluble;**welding fume	

(Contd. on page 4)



Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

Trade name: VITROBRAZE 2106®

	(Contd. of page 3
7440-47-3 ch	romium
EL (Canada)	Short-term value: C 0.1*** ppm Long-term value: 0.5* 0.01** 0.025*** mg/m³
	IARC1,ACGIH A1;*metal, inorg.**insol.;**water-sol.
EV (Canada)	
PEL (USA)	1* 0.5** mg/m³
	*metal;**inorganic compds., as Cr
REL (USA)	0.5* ** mg/m³
TI \ / /LICA\	*metal, **inorg.compds.; See Pocket Guide App. C
TLV (USA)	0.5 mg/m³
7440-21-3 sil	····
EL (Canada)	
EV (Canada)	
DEI (110A)	total dust
PEL (USA)	15* 5** mg/m³
REL (USA)	*total dust **respirable fraction 10* 5** mg/m³
REL (USA)	*total dust **respirable fraction
TLV (USA)	TLV withdrawn
7439-98-7 mg	
EL (Canada)	3* 10** mg/m³
(23, 3, 2, 3, 2, 3, 2, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3,	as Mo; *respirable **inhalable
EV (Canada)	10* 3** 0.5*** mg/m³
	metal,insol.compd.:*inh;**resp;sol.compd.:***resp
PEL (USA)	5* 15** mg/m³
	as Mo;*soluble compds.,**insol.compds.:total dust
TLV (USA)	10* 3** 0.5*** mg/m³
	insoluble compds.:*I,**R;***soluble compds.: R
7440-50-8 co	
EL (Canada)	1* 0.2** mg/m³
	*dusts and mists; **fume
EV (Canada)	0.2* 1** mg/m³
DEL (110A)	as copper, *fume;**dust and mists
PEL (USA)	1* 0.1** mg/m³
REL (USA)	as Cu *dusts and mists **fume 1* 0.1** mg/m³
KEL (USA)	as Cu *dusts and mists **fume
TLV (USA)	1* 0.2** mg/m ³
124 (00A)	*dusts and mists; **fume; as Cu
	1 4440 4.14 1.110, 40 04

• Additional Occupational Exposure Limit Values for possible hazards during processing:

If the occurrence of chrome (VI) compounds cannot be ruled out, the appropriate workplace-related limit values must also be monitored!

- Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

· Breathing equipment:



In the case of exceeding the limit values, breathing apparatus must be worn.

Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P2 or P3, for example:

- Full face mask (EN 136)
- Breathing mask (EN 149) FFP2 or FFP3
- 10 times the limit value (FFP2)

30 times the limit value (FFP3)

Recommendation: P3

(Contd. on page 5)



acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

Trade name: VITROBRAZE 2106®

(Contd. of page 4)

Protection of hands:



Wearing of gloves with a high cutting protection class is recommended for handling the bands.

The following applies due to the ingredients:

Avoid repeated and prolonged contact with the skin, use protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

- Penetration time of glove material -
- Eye protection:



Tightly sealed goggles (EN 166)

· Limitation and supervision of exposure into the environment

The legal issue values and limitations are to be paid attention!

9 Physical and chemical properties

- Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Strip
Color: Metallic
Odourless

PH-value: Not applicable.

Change in condition
Melting point/Melting range (approx): 1040°C

Auto igniting:	Not applicable
Danger of explosion:	Not applicable
Vapor pressure:	Not determined.

• Density (approx) at 20°C: 7.5 g/cm³
• Relative density Not determined.

• Solubility in / Miscibility with

Water: Insoluble.

• Other information No further relevant information available.

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions

Hydrogen is released in contact with acid which can cause explosive gas mixtures.

- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

- USA



acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

Trade name: VITROBRAZE 2106®

(Contd. of page 5)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values:

The following applies for the pure substance (here: nickel):

7440-02-0 nickel

Oral LD50 > 9000 mg/kg (rat)

- Primary irritant effect:
- on the skin: see sensitization
- on the eye:

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

Sensitization:

In the case of repeated and prolonged contact with the skin with metallic nickel there is a possibility of sensitization.

Subacute to chronic toxicity:

Nickel in the form of a respirable dust is under suspicion as a possible cause of cancer in humans (Carc.2 (Cat. 2) / CLP-Verordnung)

• Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation: Observe offical regulations.
- Uncleaned packagings: Not applicable

14 Transport information

- Transport/Additional information:
- Land transport DOT / TDG
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

(Contd. on page 7)



acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

Trade name: VITROBRAZE 2106®

(Contd. of page 6)

- Air transport ICAO-TI and IATA-DGR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

15 Regulatory information

None of the ingredient is listed.

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

Section 355 (extremely hazardous substances):

Section 313 (Specific toxic chemical listings):

7440-02-0 nickel

7440-47-3 chromium

7440-50-8 copper

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- Chemicals known to cause cancer:

7440-02-0 nickel

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Cancerogenity categories

7440-47-3 chromium 7440-50-8 copper D	l	• EPA (Envi	ronmental Protection Agency)	
7440-50-8 copper D	ſ	7440-47-3	chromium	D
		7440-50-8	copper	D

• IARC (International Agency for Research on Cancer)		
7440-02-0	nickel	2B
7440-47-3	chromium	3

• NTP (National Toxicology Program)
7440-02-0 | nickel

• TLV (Threshold Limit Value established by ACGIH)		
7440-02-0	nickel	A5
7440-47-3	chromium	A4
7439-98-7	molybdenum	A3

MAK (German Maximum Workplace Concentration)

7440-02-0 | nickel | 1

• NIOSH-Ca (National Institute for Occupational Safety and Health)
7440-02-0 | nickel

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- National regulations:
- Other regulations, limitations and prohibitive regulations
- guidelines 67/548/ECC, 1999/45/EC
- 1272/2008/EG (CLP)
- 1907/2006/EG (REACH)

(Contd. on page 8)

R



acc. to ISO/DIS 11014

Printing date 01/26/2012 Reviewed on 01/26/2012

Trade name: VITROBRAZE 2106®

- German Hazardous Substances

(Contd. of page 7)

Chemical safety assessment: Void (for articles)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

H228 Flammable solid.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

R11 Highly flammable.

R40 Limited evidence of a carcinogenic effect.

May cause sensitization by skin contact. R43

R48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.

Department issuing MSDS:

Department HT-F Tel. 06181/38-2045

• Contact:

Environmental Protection Department

Tel. 06181/38-2359

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

ACGIH: American Conference of Governmental Industrial Hygienists

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Sources

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe
- BIA-Gefahrstoffdatenbank