

(MSDS)

Printing date 03/12/2020 Version - No. 3 Reviewed on 03/12/2020

1 Identification

Product identifier

• Trade name: CALORIVAC® H; -HS

Article number:

CALORIVAC® H, CALORIVAC® HS Parts / granulated material (> 100 µm)

® registered trademark of VACUUMSCHMELZE GmbH & Co. KG

• Material Safety Data Sheet - no.: IB130

Application of the substance / the mixture

Magnetocaloric material, e.g. Refrigerators, Freezers, Air conditioning equipment, heat pumps, energy conversion

• Details of the supplier of the safety data sheet

• Manufacturer/Supplier:

VACUUMSCHMELZE GmbH & Co.KG

Grüner Weg 37 D-63450 Hanau

datasheet@vacuumschmelze.com

• Information department: Environmental Protection Department

• Emergency telephone number: Tel. no.: (**49) 6181/38-0 Emergency tel. no.: via (**49) 6181/38-0

2 Hazard(s) identification

Classification (substance or mixture)

Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006.

For articles there is no obligation to classify acc. to CLP -Regulation.

GHS label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

Additional VAC information:

In the case of dust-producing processing, we recommend observance of the following warnings:

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

Precautionary statements

Do not breathe dust.

Use personal protective equipment as required.

If on skin: Wash with plenty of water.

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

(Contd. on page 2)



(MSDS)

Printing date 03/12/2020 Version - No. 3 Reviewed on 03/12/2020

Trade name: CALORIVAC® H; -HS

(Contd. of page 1)

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization:
- Description: La-Fe- Alloy (Parts / granulated material)
- Dangerous components:

The classifications given below reflect the classification of each <u>pure substance</u> respectively and are intended for information only

The legal classifications of the pure substances (harmonized classification according to substance list of the Annex VI of the CLP Regulation) got complemented, insofar as additional substance-specific information from accessible data sources (e.g. TRGS 905, toxicological studies) for health hazards and / or physical hazards are available.

CAS: 7439-89-6 EINECS: 231-096-4	iron (compact form)	rest%
CAS: 7439-96-5 EINECS: 231-105-1	manganese	≤6%
CAS: 7440-21-3 EINECS: 231-130-8	silicon	≤6%
CAS: 7440-48-4 EINECS: 231-158-0 Index number: 027-001-00-9	cobalt ❖ Resp. Sens. 1, H334; Carc. 1B, H350; Repr. 1B, H360; ❖ Acute Tox. 4, H302; Skin Sens. 1, H317	< 0.2%

NON-hazardous Ingredients

CAS: 7439-91-0	lanthanum	<20%
EINECS: 231-099-0		

- Remark to the composition: Product contains bound hydrogen. (≤ 0,3%)
- Additional information:

For the wording of the listed hazard phrases refer to section 16.

Additional information for Cobalt:

See also Chapter 11

4 First-aid measures

- Description of first aid measures
- After inhalation:

If metal vapours or solid dusts have been inhaled:

Get the affected person out in the fresh air and call a doctor.

After skin contact:

Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Consult a doctor if the symptoms persist.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 03/12/2020 Version - No. 3 Reviewed on 03/12/2020

Trade name: CALORIVAC® H; -HS

(Contd. of page 2)

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

Non-combustible.

Extinguishing agents must be adapted to the environment.

Special hazards arising from the substance or mixture

In case of fire, hydrogen could be released!

Formation of toxic smoke / fumes (metal / metal oxides) is possible during heating or in case of fire. Do not inhale fumes.

- Advice for firefighters
- Protective equipment: Do not inhale fumes.

6 Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

- Personal precautions, protective equipment and emergency procedures No special measures required.
- Environmental precautions: No special measures required.
- Methods and material for containment and cleaning up: No special measures required.
- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:
- Precautions for safe handling

No safety precautions are necessary in the delivered form.

The appropriate industrial and environmental safety measures

must be taken for processing steps which cause dust (see also section 8):

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

- Information about protection against explosions and fires: In case of fire, hydrogen could be released!
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Storage class: Not applicable
- Specific end use(s) No further relevant information available.

ISA -



Material Safety Data Sheet (MSDS)

Printing date 03/12/2020 Version - No. 3 Reviewed on 03/12/2020

Trade name: CALORIVAC® H; -HS

(Contd. of page 3)

8 Exposure controls/personal protection

• Additional information about design of technical systems:

Provide suction with filtering for good airing and ventilation of the work area during processing steps which cause dust. Air return is only permitted in exceptional cases.

If industrial vacuum cleaners are used, these must have dust class H (DIN EN 60335-2-69).

Suitable breathing apparatus must be used during repair and maintenance work to suction systems, especially when changing filters (see personal safety equipment).

Control parameters

• Components with limit values that require monitoring at the workplace:

	n (compact form)
EV (Canada)	Long-term value: 1* 5** mg/m³
	as iron;*salts, water-soluble;**welding fume
7439-96-5 ma	inganese
PEL (USA)	Ceiling limit value: 5 mg/m³ as Mn
REL (USA)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ fume, as Mn
TLV (USA)	Long-term value: 0.02* 0.1** mg/m³ as Mn; *respirable **inhalable fraction
IOELV (EU)	Long-term value: 0.2* 0.05** mg/m³ as Mn; *inhalable, **respirable fraction
EL (Canada)	Long-term value: 0.2; 0.02* mg/m³ as Mn; R, *respirable
EV (Canada)	Long-term value: 0.2 mg/m³ as manganese
7440-21-3 sil	con
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction
EV (Canada)	Long-term value: 10 mg/m³ total dust
7440-48-4 co	
PEL (USA)	Long-term value: 0.1* mg/m³ as Co; *for metal dust and fume
REL (USA)	Long-term value: 0.05 mg/m³ as Co; metal dust & fume
TLV (USA)	Long-term value: 0.02* mg/m³ *inh. fraction; DSEN, RSEN, BEI
EL (Canada)	Long-term value: 0.02 mg/m³ total: IARC 2B, S(D), S(R)
EV (Canada)	Long-term value: 0.1 mg/m ³

• DNELs

DNELs for OSH purposes

In Germany, occupational exposure limits (AGW) of the Technical Rules on Hazardous Substances (TRGS) 900 continue to constitute workplace atmospheric limit values that are binding upon employers. Should no AGW and for example no maximum workplace concentration (MAK value) of the German Research Foundation (DFG) be (Contd. on page 5)



Material Safety Data Sheet (MSDS)

Reviewed on 03/12/2020 Printing date 03/12/2020 Version - No. 3

Trade name: CALORIVAC® H; -HS

(Contd. of page 4)

available, the employer must also consider the DNEL during risk assessment. (Source: Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA)) current values are available: http://www.dguv.de/ifa/gestis/gestis-dnel-liste/index.jsp.

7440-4	7440-48-4 cobalt				
Inhalati	/e Langzeitexposition - Inhalation - lokale Wirkung	0.04 mg/m³ (Ind)			
		0.0063 mg/m³ (Consumer)			
Ingredients with biological limit values:					
7440-40-4					

7440-48-4 cobalt

BEI (USA) 15 µg/L

Medium: urine

Time: end of shift at end of workweek Parameter: Cobalt (background)

1 µg/L

Medium: blood

Time: end of shift at end of workweek

Parameter: Cobalt (background, semi-quantitative)

Additional information:

The lists that were valid during the creation were used as basis.

GESTIS International Limit Values:

http://www.dguv.de/ifa/Gefahrstoffdatenbanken/GESTIS-Internationale-Grenzwerte-für-chemische-Substanzenlimit-values-for-chemical-agents/index.jsp

Exposure controls

• Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Breathing equipment:



In the case of dust formation (limit value exceeded), breathing apparatus must be worn. Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P2 or P3

According to the guideline "42 CFR Part 84 Respiratory Protective Devices" the following respiratory masks / particel filter are recommend: N 95 or N 99

Protection of hands:



Avoid repeated and prolonged contact with the skin, use protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

Material of gloves

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

· Penetration time of glove material -

Eye protection:



In the event of larger quantities of dust:

Wear protective glasses / EN 166, poss. with side protection.

(Contd. on page 6)



(MSDS)

Printing date 03/12/2020 Reviewed on 03/12/2020 Version - No. 3

Trade name: CALORIVAC® H; -HS

(Contd. of page 5)

Limitation and supervision of exposure into the environment

The legal issue values and limitations are to be paid attention!

9 Physical and chemical properties

• Information on basic physical and chemical properties

General Information

Appearance:

Parts / granulated material Form:

Color: Metallic · Odor: Metallic

• pH-value: Not applicable.

Change in condition

Melting point/Melting range (approx): 1,180 °C

Auto igniting: Not applicable Danger of explosion: Not applicable

Vapor pressure: Not determined.

• Density (approx) at 20 °C: 7.2 g/cm³ Relative density Not determined.

• Solubility in / Miscibility with

Water: Insoluble.

• Partition coefficient (n-octanol/water): Not determined.

 Other information No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: Release of hydrogen at temperatures >200°C
- Possibility of hazardous reactions

Hydrogen is released in contact with acid which can cause explosive gas mixtures.

- Conditions to avoid Temperatures > 200°C
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values:

The following applies for the pure substances:

7440-48-4	7440-48-4 cobalt		
Oral	LD50	550 mg/kg (rat)	
Inhalative		mg/l (rat) siehe zusätzlicher toxikologischer Hinweis / see additional toxicological information	

(Contd. on page 7)



Printing date 03/12/2020 Version - No. 3 Reviewed on 03/12/2020

Trade name: CALORIVAC® H; -HS

(Contd. of page 6)

Primary irritant effect:

- on the skin: No irritant effect.
- on the eye:

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

- Sensitization: No sensitizing effects known.
- Additional toxicological information:

Subsequent users should be aware of the fact that Co-metal fine powder are classified as "acute toxic if inhaled, Category 1" (no legal classification); LC50 4hr ≤0,05 mg/l.

In case the subsequent use of product generates fine Co-metal particles (e.g. dust), protection measures such as described in Chapter 7 and 8 of this information sheet must be applied.

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Carcinogenic categories

IARC (International Agency for Research on Cancer)		
7440-48-4	cobalt	2B
• NTP (Natio	onal Toxicology Program)	
7440-48-4	cobalt	R
OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Alloys in solid form do not pose an ecological threat.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation: Observe offical regulations.
- Uncleaned packagings: Not applicable

USA ·



Printing date 03/12/2020 Version - No. 3 Reviewed on 03/12/2020

Trade name: CALORIVAC® H; -HS

(Contd. of page 7)

14 Transport information

- Transport/Additional information:
- ADR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Air transport ICAO-TI and IATA-DGR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):
 - 7439-96-5 manganese
- 7440-48-4 cobalt
- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Hazardous Air Pollutants
- 7439-96-5 manganese
- 7440-48-4 cobalt
- Proposition 65
- Chemicals known to cause cancer:
- 7440-48-4 cobalt
- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

7440-48-4 cobalt

А3

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- National regulations:
- Information about limitation of use:

Employment restrictions concerning young persons must be observed. Employment restrictions concerning pregnant and lactating women must be observed.

- Technical instructions (air): The emission values and limitations must be observed!
- Water hazard class: Alloys in solid form do not pose an ecological threat.

(Contd. on page 9)



Material Safety Data Sheet (MSDS)

Reviewed on 03/12/2020 Printing date 03/12/2020 Version - No. 3

Trade name: CALORIVAC® H; -HS

(Contd. of page 8)

Other regulations, limitations and prohibitive regulations

- 1272/2008/EG (CLP)

- 1907/2006/EG (REACH)
- German Hazardous Substances
- Chemical safety assessment: Void (for articles)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer. Route of exposure: Inhalation.

H360 May damage fertility or the unborn child.

Department issuing SDS:

Department OPS-C SE Tel. 06181/38-2045

• Contact:

Environmental Protection Department

Tel. 06181/38-2359

Date of preparation / last revision 03/12/2020 / 2

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4
Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 1B: Carcinogenicity – Category 1B
Repr. 1B: Reproductive toxicity – Category 1B

Sources

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe