

for articles

Printing date 22.06.2018 Version number 1 Revision: 22.06.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

• 1.1 Product identifier

• Trade name: REMAVAC 20®

• Detailed descriptions:

® registered trademark of VACUUMSCHMELZE GmbH & Co. KG

• Information sheet - no.: IB137

• Remarks for information sheet

Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006.

Articles are not subject to any legal obligation concerning production and distribution of material safety data sheets. The detailed information usually shown in a safety data sheet will be provided in the form of an 'Information sheet for articles' for specific alloys.

However, we expressly point out that these information sheets for articles are voluntarily produced data sheets which are not governed by the requirements of the REACH regulation.

- 1.2 Relevant identified uses of the substance or mixture and uses advised against Not applicable
- Application of the article: semi-finished products and parts
- 1.3 Details of the supplier of the information sheet
- Manufacturer/Supplier:

VACUUMSCHMELZE GmbH & Co.KG Grüner Weg 37 D-63450 Hanau

datasheet@vacuumschmelze.com

- Further information obtainable from: Environmental Protection Department
- 1.4 Emergency telephone number:

Tel. no.: (**49) 6181/38-0 Emergency tel. no.: via (**49) 6181/38-0

SECTION 2: Hazards identification

• 2.2 Classification (substance or mixture)

Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

For articles there is no obligation to classify acc. to CLP -Regulation.

• 2.2 Labelling according to Regulation (EC) No 1272/2008

Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

Additional VAC information:

In the case of dust-producing processing, we recommend observance of the following warnings:

• Hazard statements

May cause an allergic skin reaction.

May cause cancer by inhalation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapours/spray.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

Get medical advice/attention if you feel unwell.

(Contd. on page 2)



for articles

Printing date 22.06.2018 Version number 1 Revision: 22.06.2018

Trade name: REMAVAC 20®

(Contd. of page 1)

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

• 3.2 Chemical characterization:

• Description: Metal in compact form

Components(composition):

The classifications given below reflect the classification of each <u>pure substance</u> respectively and are intended for information only

The legal classifications of the pure substances (harmonized classification according to substance list of the Annex VI of the CLP Regulation) got complemented, insofar as additional substance-specific information from accessible data sources (e.g. TRGS 905, toxicological studies) for health hazards and / or physical hazards are available.

The concentration of cobalt might be $\geq 0.1\%$ (impurities)

	The concentration of cobat might be 2 0,1 % (impurities)				
	CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-00-7	nickel	~ 7%		
	CAS: 7439-96-5 EINECS: 231-105-1 RTECS: OO 9275000	manganese substance with a Community workplace exposure limit	~ 6%		
	CAS: 7440-50-8 EINECS: 231-159-6 RTECS: GL 5325000	copper substance with a Community workplace exposure limit	<3%		
	CAS: 7440-48-4 EINECS: 231-158-0 Index number: 027-001-00-9 RTECS: GF 8750000	cobalt Resp. Sens. 1, H334; Carc. 1B, H350i; Repr. 2, H361f; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 4, H413	<0.4%		
ĺ	NON-hazardous Ingredients				

NON-hazardous Ingredients

CAS: 7439-89-6	iron (compact form)	rest%
EINECS: 231-096-4		
RTECS: NO 4565500		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

After inhalation:

If metal vapours or dusts have been inhaled:

Get the affected person out in the fresh air and call a doctor.

After skin contact:

Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Consult a doctor if the symptoms persist.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



for articles

Printing date 22.06.2018 Version number 1 Revision: 22.06.2018

Trade name: REMAVAC 20®

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Non-combustible.

Extinguishing agents must be adapted to the environment.

• 5.2 Special hazards arising from the substance or mixture

Formation of toxic smoke / fumes (metal / metal oxides) is possible during heating or in case of fire. Do not inhale fumes.

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

SECTION 6: Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

- 6.1 Personal precautions, protective equipment and emergency procedures No special measures required.
- 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: No special measures required.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

•7.1 Precautions for safe handling

No safety precautions are necessary in the delivered form.

The appropriate industrial and environmental safety measures

must be taken for processing steps which cause dust

(see also section 8):

Prevent formation of dust.

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

- Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Not applicable
- Storage class: Not applicable
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities:

Provide suction with filtering for good airing and ventilation of the work area during processing steps which cause dust.

(Contd. on page 4)



for articles

Revision: 22.06.2018 Printing date 22.06.2018 Version number 1

Trade name: REMAVAC 20®

(Contd. of page 3)

If industrial vacuum cleaners are used, these must have dust class H (DIN EN 60335-2-69). Suitable breathing apparatus must be used during repair and maintenance work to suction systems, especially when changing filters (see personal safety equipment).

• 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

For International Limit Values see Additional information below.

7440-02-0 nickel		
AGW (Germany)	Long-term value: 0.006 A mg/m³ 8(II);AGS, 24, Sh, Y	
7439-96-5 manga	7439-96-5 manganese	
AGW (W)	Long-term value: 0.5 E mg/m³	
IOELV (EU)	Long-term value: 0.2* 0.05** mg/m³ as Mn; *inhalable, **respirable fraction	
AGW (Germany)	Long-term value: 0.02A; 0.2E mg/m³ 8(II);DFG,Y,10, 20	
7440-50-8 coppe	7440-50-8 copper	
DFG (Germany)	Long-term value: 0.1 E mg/m³ als Cu	
MAK (Germany)	Long-term value: 0.01 A mg/m³ als Cu	
7440-48-4 cobalt		
ERB (Germany)	s. TRGS 910	

DNELs

DNELs for OSH purposes

In Germany, occupational exposure limits (AGW) of the Technical Rules on Hazardous Substances (TRGS) 900 continue to constitute workplace atmospheric limit values that are binding upon employers. Should no AGW and for example no maximum workplace concentration (MAK value) of the German Research Foundation (DFG) be available, the employer must also consider the DNEL during risk assessment.

(Source: Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA)) current values are available: http://www.dguv.de/ifa/gestis/gestis-dnel-liste/index.jsp.

7440-02-0 Inhalative		0.05 mg/m³ (Ind)	
	Long-term exposure - inhalation - systemic effects	• ,	
7440-48-4 cobalt			
Inhalative	Long-term exposure - inhalation - local effects	0.04 mg/m³ (Ind)	
		0.0063 mg/m³ (Consumer)	
• Ingredients with biological limit values:			
7439-96-5 manganese			

BGW (Germany) 20 µg/l

Untersuchungsmaterial: Vollblut

Probennahmezeitpunkt: bei Langzeitexposition: Nach mehreren vorangegangenen Schichten,

Expositionsende bzw. Schichtende

Parameter: Mangan

Additional Occupational Exposure Limit Values for possible hazards during processing:

Compliance with the general dust limit value(s) (lung penetrating and/or inhalable fraction) must be ensured.

Additional information:

- The lists valid during the making were used as basis.
- GESTIS International Limit Values:

http://www.dguv.de/ifa/Gefahrstoffdatenbanken/GESTIS-Internationale-Grenzwerte-für-chemische-Substanzenlimit-values-for-chemical-agents/index.jsp

(Contd. on page 5)



for articles

Printing date 22.06.2018 Version number 1 Revision: 22.06.2018

Trade name: REMAVAC 20®

(Contd. of page 4)

• 8.2 Exposure controls

Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Respiratory protection:



In the case of dust formation (limit value exceeded), breathing apparatus must be worn. Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P2 or P3, for example:

- Full face mask (EN 136)
- Breathing mask (EN 149) FFP2 or FFP3
- 10 times the limit value (FFP2)
- 30 times the limit value (FFP3)

Recommendation: P3

Protection of hands:



Avoid repeated and prolonged contact with the skin, use protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

Material of gloves

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

- Penetration time of glove material -
- Eye protection:



In the event of larger quantities of dust:

Wear protective glasses / EN 166, poss. with side protection.

• Limitation and supervision of exposure into the environment

The legal issue values and limitations are to be paid attention!

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Semi-finished products/parts: e.g. strip, wire, parts and bars

Colour: Metallic
• Odour: Odourless

• pH-value: Not applicable.

Change in condition

Melting point/Melting range (approx.): 1,400-1,500 °C

 Auto-ignition temperature: 	Not applicable
• Explosive properties:	Not applicable
Vapour pressure:	Not determined.

(Contd. on page 6)



for articles

Revision: 22.06.2018 Printing date 22.06.2018 Version number 1

Trade name: REMAVAC 20®

(Contd. of page 5)

Density (approx.) at 20 °C: ~7.8 g/cm³ Relative density Not determined.

• Solubility in / Miscibility with

water: Insoluble.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions

Hydrogen is released in contact with acid which can cause explosive gas mixtures.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values:

The following applies for the pure substance (here: nickel):

7440-02-0	7440-02-0 nickel		
Oral	LD50	>9,000 mg/kg (rat)	
7440-48-4	7440-48-4 cobalt		
Oral	LD50	550 mg/kg (rat)	
Inhalative			
		siehe zusätzlicher toxikologischer Hinweis / see additional toxicological information	

- Primary irritant effect:
- Skin corrosion/irritation see sensitization
- Serious eye damage/irritation

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

Respiratory or skin sensitisation

Contains cobalt (< 1%). May produce an allergic reaction.

May cause an allergic skin reaction.

- Additional toxicological information: --
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity

May cause cancer by inhalation.

- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

• Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



for articles

Printing date 22.06.2018 Version number 1 Revision: 22.06.2018

Trade name: REMAVAC 20®

(Contd. of page 6)

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Not known to be hazardous to water.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Observe offical regulations.
- Uncleaned packaging: Not applicable

SECTION 14: Transport information

- Transport/Additional information:
- Land transport ADR/RID (cross-border):
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Air Transport ICAO-TI and IATA-DGR:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 27
- National regulations:
- Other regulations, limitations and prohibitive regulations
 - e.g.
- 1272/2008/EG (CLP)
- 1907/2006/EG (REACH)
- German Hazardous Substances
- 15.2 Chemical safety assessment: Void (for articles)

(Contd. on page 8)



for articles

Revision: 22.06.2018 Printing date 22.06.2018 Version number 1

Trade name: REMAVAC 20®

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350i May cause cancer by inhalation.

H351 Suspected of causing cancer.

H361f Suspected of damaging fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

Department issuing SDS:

Department OPS-C SE Tel. 06181/38-2045

• Contact:

Environmental Protection Department

Tel. 06181/38-2359

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

Sources

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe