

for articles

Printing date 12.12.2019 Version number 2 Revision: 12.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

• 1.1 Product identifier

• Trade name: VITROVAC ®

• Detailed descriptions:

VITROVAC 6018 W18, - 6006 A10, - 6120 V20, - 6125 V25

® registered trademark of VACUUMSCHMELZE GmbH & Co. KG

• Information sheet - no.: IB38

Remarks for information sheet

Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006.

Articles are not subject to any legal obligation concerning production and distribution of material safety data sheets. The detailed information usually shown in a safety data sheet will be provided in the form of an 'Information sheet for articles' for specific alloys.

However, we expressly point out that these information sheets for articles are voluntarily produced data sheets which are not governed by the requirements of the REACH regulation.

- 1.2 Relevant identified uses of the substance or mixture and uses advised against Not applicable
- Application of the article: semi-finished products and parts
- 1.3 Details of the supplier of the information sheet
- Manufacturer/Supplier:

VACUUMSCHMELZE GmbH & Co.KG Grüner Weg 37 D-63450 Hanau

2 00 100 1101100

datasheet@vacuumschmelze.com

- Further information obtainable from: Environmental Protection Department
- 1.4 Emergency telephone number: Tel. no.: (**49) 6181/38-0 Emergency tel. no.: via (**49) 6181/38-0

SECTION 2: Hazards identification

2.2 Classification (substance or mixture)

Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

For articles there is no obligation to classify acc. to CLP -Regulation.

• 2.2 Labelling according to Regulation (EC) No 1272/2008

Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

Additional VAC information:

In the case of dust-producing processing, we recommend observance of the following warnings :

Hazard statements

Harmful if swallowed.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer by inhalation. Route of exposure: Inhalation.

May damage fertility.

Causes damage to organs through prolonged or repeated exposure.

May cause long lasting harmful effects to aquatic life.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapours/spray.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

(Contd. on page 2)



for articles

Revision: 12.12.2019 Printing date 12.12.2019 Version number 2

Trade name: VITROVAC ®

(Contd. of page 1)

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

Get medical advice/attention if you feel unwell.

2.3 Other hazards

Danger of accident!

Always wear protective clothing, protective glasses and safety gloves when handling the bands.

- The bands have sharp edges. There is a danger of (serious) injury from cuts.
- The bands can split and cause (serious) cuts when bent excessively
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterization:

• Description: Metal in compact form

• Components(composition):

The classifications given below reflect the classification of each pure substance respectively and are intended for information only

The legal classifications of the pure substances (harmonized classification according to substance list of the Annex VI of the CLP Regulation) got complemented, insofar as additional substance-specific information from accessible data sources (e.g. TRGS 905, toxicological studies) for health hazards and / or physical hazards are available.

CAS: 7440-48-4 EINECS: 231-158-0 Index number: 027-001-00-9 RTECS: GF 8750000	cobalt Resp. Sens. 1, H334; Carc. 1B, H350i; Repr. 1B, H360F; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 4, H413	35-70%
CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-00-7	nickel	15-46%
CAS: 7440-42-8 EINECS: 231-151-2 RTECS: ED 7350000	oron Acute Tox. 4, H302	<4%
CAS: 7439-96-5 EINECS: 231-105-1 RTECS: OO 9275000	manganese substance with a Community workplace exposure limit	<2%

NON-hazardous Ingredients		
CAS: 7440-21-3 EINECS: 231-130-8	silicon	2-8%
CAS: 7439-89-6 EINECS: 231-096-4 RTECS: NO 4565500	iron (compact form)	rest%

• Remark to the composition:

* The manganese concentration mentioned only applies for the alloys VITROVAC 6120 V20 and - 6125 V25.

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Additional information for Cobalt:

See also Chapter 11



for articles

Printing date 12.12.2019 Version number 2 Revision: 12.12.2019

Trade name: VITROVAC®

(Contd. of page 2)

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation:

If metal vapours or dusts have been inhaled:

Get the affected person out in the fresh air and call a doctor.

After skin contact:

Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

• After eye contact:

Foreign bodies must be removed, consult a doctor if necessary.

Beware of metal splinters - Consult a doctor immediately.

- After swallowing: Consult a doctor if the symptoms persist.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Non-combustible.

Extinguishing agents must be adapted to the environment.

• 5.2 Special hazards arising from the substance or mixture

Formation of toxic smoke / fumes (metal / metal oxides) is possible during heating or in case of fire. Do not inhale fumes.

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

SECTION 6: Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

- 6.1 Personal precautions, protective equipment and emergency procedures No special measures required.
- 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: No special measures required.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling

Danger of accident!

Always wear protective clothing, protective glasses and safety gloves when handling the bands.

- The bands have sharp edges. There is a danger of (serious) injury from cuts.
- The bands can split and cause (serious) cuts when bent excessively.

No more safety precautions are necessary in the delivered form.

The appropriate industrial and environmental safety measures

must be taken for processing steps which cause dust

(Contd. on page 4)



for articles

Printing date 12.12.2019 Version number 2 Revision: 12.12.2019

Trade name: VITROVAC®

(Contd. of page 3)

(see also section 8):

Prevent formation of dust.

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

- Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Not applicable
- Storage class: Not applicable
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities:

Provide suction with filtering for good airing and ventilation of the work area during processing steps which cause dust. Air return is only permitted in exceptional cases.

If industrial vacuum cleaners are used, these must have dust class H (DIN EN 60335-2-69).

Suitable breathing apparatus must be used during repair and maintenance work to suction systems, especially when changing filters (see personal safety equipment).

• 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

For International Limit Values see Additional information below.

	To the material Entite Values 500 / talkerial mierrialist below.	
7440-48-4 cobalt	7440-48-4 cobalt	
ERB (Germany)	0.5 μg/m³ (A) bzw. 5μg/m³ (A)	
MAK (Germany)	einatembare Fraktion; vgl.Abschn.XIII	
7440-02-0 nickel	7440-02-0 nickel	
AGW (Germany)	Long-term value: 0.006A; 0.030E* mg/m³ 8(II);AGS, 24, Sh, Y, 10*, 31*	
7440-42-8 boron		
MAK (Germany)	Long-term value: 0.75E mg/m ³	
7439-96-5 mang	7439-96-5 manganese	
AGW (W)	Long-term value: 0.5 E mg/m³	
IOELV (EU)	Long-term value: 0.2* 0.05** mg/m³ as Mn; *inhalable, **respirable fraction	
AGW (Germany)	Long-term value: 0.02A; 0.2E mg/m³ 8(II);DFG,Y,10, 20	

• DNELs

DNELs for OSH purposes

In Germany, occupational exposure limits (AGW) of the Technical Rules on Hazardous Substances (TRGS) 900 continue to constitute workplace atmospheric limit values that are binding upon employers. Should no AGW and for example no maximum workplace concentration (MAK value) of the German Research Foundation (DFG) be available, the employer must also consider the DNEL during risk assessment.

(Source: Institut für Årbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA)) current values are available: http://www.dguv.de/ifa/gestis/gestis-dnel-liste/index.jsp.

7440-48-4 cobalt		
Inhalative Long-term exposure - inhalation - local effects	0.04 mg/m³ (Ind)	
		(Contd. on page 5)

. F



for articles

Revision: 12.12.2019 Printing date 12.12.2019 Version number 2

Trade name: VITROVAC®

		(Contd. of page 4)		
		0.0063 mg/m³ (Consumer)		
7440-02-0	7440-02-0 nickel			
Inhalative	Long-term exposure - inhalation - local effects	ng-term exposure - inhalation - local effects 0.05 mg/m³ (Ind)		
	Long-term exposure - inhalation - systemic effects 0.05 mg/m³ (Ind)			
• Ingredien	• Ingredients with biological limit values:			
7439-96-5	7439-96-5 manganese			
BGW (Gei	BGW (Germany) 20 μg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten, Expositionsende bzw. Schichtende Parameter: Mangan			

Additional Occupational Exposure Limit Values for possible hazards during processing:

Compliance with the general dust limit value(s) (lung penetrating and/or inhalable fraction) must be ensured. If the occurrence of Boric acid/ Boron oxide cannot be ruled out, the appropriate workplace-related limit values must also be monitored!

The AGW for nickel is to be used only for nickel metal.

For thermal processes in the presence of atmospheric oxygen, oxidic nickel compounds must always be assumed and the ERB (TRGS 910) must be applied.

Additional information:

- The lists valid during the making were used as basis.
- GESTIS International Limit Values:

http://www.dguv.de/ifa/Gefahrstoffdatenbanken/GESTIS-Internationale-Grenzwerte-für-chemische-Substanzenlimit-values-for-chemical-agents/index.jsp

• 8.2 Exposure controls

• Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Respiratory protection:



In the case of dust formation (limit value exceeded), breathing apparatus must be worn. Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P2 or P3, for example:

- Full face mask (EN 136)
- Breathing mask (EN 149) FFP2 or FFP3

10 times the limit value (FFP2)

30 times the limit value (FFP3)

Recommendation: P3

Protection of hands:



Avoid repeated and prolonged contact with the skin, use protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

Material of gloves

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

· Penetration time of glove material -

(Contd. on page 6)



for articles

Printing date 12.12.2019 Version number 2 Revision: 12.12.2019

Trade name: VITROVAC ®

(Contd. of page 5)

• Eye protection:



In the event of larger quantities of dust:

Wear protective glasses / EN 166, poss. with side protection.

• Limitation and supervision of exposure into the environment

The legal issue values and limitations are to be paid attention!

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Strip
Colour: Metallic

Odourless

PH-value: Not applicable.

Change in condition

• Auto-ignition temperature:

Melting point/Melting range (approx.): 1,100-1,200 °C

• Explosive properties: Not applicable
• Vapour pressure: Not determined.

Density (approx.) at 20 °C:
 Relative density
 7.7-8 g/cm³
 Not determined.

• Solubility in / Miscibility with

water: Insoluble.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Not applicable

• 10.3 Possibility of hazardous reactions

Hydrogen is released in contact with acid which can cause explosive gas mixtures.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity

Harmful if swallowed.

• LD/LC50 values:

The following applies for the pure substances:

(Contd. on page 7)



for articles

Printing date 12.12.2019 Version number 2 Revision: 12.12.2019

Trade name: VITROVAC®

(Contd. of page 6)

7440-48-4	7440-48-4 cobalt		
Oral	LD50	550 mg/kg (rat)	
Inhalative	LC50/4 h	mg/l (rat)	
		siehe zusätzlicher toxikologischer Hinweis / see additional toxicological information	
7440-02-0	7440-02-0 nickel		
Oral	LD50	>9,000 mg/kg (rat)	
7440-42-8	7440-42-8 boron		
Oral	LD50	650 mg/kg (rat)	

• Primary irritant effect:

- Skin corrosion/irritation see sensitization
- · Serious eye damage/irritation

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Additional toxicological information:

Subsequent users should be aware of the fact that Co-metal fine powder are classified as "acute toxic if inhaled, Category 1" (no legal classification); LC50 4hr ≤0,05 mg/l.

In case the subsequent use of product generates fine Co-metal particles (e.g. dust), protection measures such as described in Chapter 7 and 8 of this information sheet must be applied.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity

May cause cancer by inhalation. Route of exposure: Inhalation.

Reproductive toxicity

May damage fertility.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Alloys in solid form do not pose an ecological threat.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Observe offical regulations.

(Contd. on page 8)



for articles

Printing date 12.12.2019 Version number 2 Revision: 12.12.2019

Trade name: VITROVAC®

(Contd. of page 7)

Uncleaned packaging: Not applicable

SECTION 14: Transport information

- Transport/Additional information:
- Land transport ADR/RID (cross-border):
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Air Transport ICAO-TI and IATA-DGR:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 27
- National regulations:
- Other regulations, limitations and prohibitive regulations

e.g.

- 1272/2008/EG (CLP)
- 1907/2006/EG (REACH)
- German Hazardous Substances
- TRGS 561 / TRGS 910
- 15.2 Chemical safety assessment: Void (for articles)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H350i May cause cancer by inhalation. Route of exposure: Inhalation.
- H351 Suspected of causing cancer. Route of exposure: Inhalation.
- H360F May damage fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H413 May cause long lasting harmful effects to aquatic life.

Department issuing SDS:

Department OPS-C SE Tel. 06181/38-2045

• Contact:

Environmental Protection Department

Tel. 06181/38-2359

(Contd. on page 9)



for articles

Printing date 12.12.2019 Version number 2 Revision: 12.12.2019

Trade name: VITROVAC ®

(Contd. of page 8)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity - oral – Category 4
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Acutatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

Sources

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe
- * Data compared to the previous version altered.