

Printing date 10/11/2011

Reviewed on 10/11/2011

1 Identification of the substance/mixture and of the company/undertaking

- Product identifier
- Trade name: VITROVAC ®
- Article number: VITROVAC 6025 C20, 6025 E30, 6025 G40, 6200 D90, 6015 W15, 6155 U55

Material Safety Data Sheet acc. to ISO/DIS 11014

- Material Safety Data Sheet no.: IB70
- Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation semi-finished products and parts
- Details of the supplier of the safety data sheet

• Manufacturer/Supplier: VACUUMSCHMELZE GmbH & Co.KG Grüner Weg 37 D-63450 Hanau

datasheet@vacuumschmelze.com

- Information department: Environmental Protection Department
- Emergency telephone number:
- Tel. no.: (**49) 6181/38-0 Emergency tel. no.: via (**49) 6181/38-0

2 Hazards identification

 Classification (substance or mixture) Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation): Not applicable Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006. For articles there is no obligation to classify acc. to CLP -Regulation. GHS label elements Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation): Not applicable
Additional VAC information:
 In the case of dust-producing processing, we recommend observance of the following warnings : Hazard statements May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause long lasting harmful effects to aquatic life. Precautionary statements Do not breathe dust/fume/gas/mist/vapours/spray. In case of inadequate ventilation wear respiratory protection. Use personal protective equipment as required. Avoid release to the environment. Do no eat, drink or smoke when using this product. Get medical advice/attention if you feel unwell.
 Other hazards Danger of accident! Always wear protective clothing, protective glasses and safety gloves when handling the bands. The bands have sharp edges. There is a danger of (serious) injury from cuts. The bands can split and cause (serious) cuts when bent excessively Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

(Contd. on page 2)

acc. to ISO/DIS 11014

Reviewed on 10/11/2011

Trade name: VITROVAC [®]

(Contd. of page 1)

3 Composition/information on ingredients

- Chemical characterization:
- Description: Metal in compact form
- Dangerous components:

The classifications given below reflect the classification of each <u>pure substance</u> respectively and are intended for information only

CAS: 7440-48-4 EINECS: 231-158-0 Index number: 027-001-00-9	cobalt	Xi R42/43 R53 � H334; � H317; H413	82-88%
CAS: 7440-21-3 EINECS: 231-130-8	silicon	▶ F R11	3-9%
CAS: 7439-89-6 EINECS: 231-096-4	iron		ca. 5%
CAS: 7439-98-7 EINECS: 231-107-2	molybdenum		≤ 3*%

• Remark to the composition: * VITROVAC 6200 D90, - 6015 W15 and - 6155 U55 don't contain any molybdenum.

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• Description of first aid measures

After inhalation:

If metal vapours or solid dusts have been inhaled: Get the affected person out in the fresh air and call a doctor.

• After skin contact: Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

• After eye contact: Foreign bodies must be removed, consult a doctor if necessary.

Beware of metal splinters - Consult a doctor immediately.

- After swallowing: Consult a doctor if the symptoms persist.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- Extinguishing media
- Suitable extinguishing agents: Non-combustible.

Extinguishing agents must be adapted to the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

• Personal precautions, protective equipment and emergency procedures No special measures required.

- Environmental precautions: No special measures required.
- Methods and material for containment and cleaning up: No special measures required.

(Contd. on page 3)



Printing date 10/11/2011



acc. to ISO/DIS 11014

Reviewed on 10/11/2011

(Contd. of page 2)

Printing date 10/11/2011

Trade name: VITROVAC [®]

Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

• Handling:

• Precautions for safe handling

Danger of accident!

Always wear protective clothing, protective glasses and safety gloves when handling the bands.

- The bands have sharp edges. There is a danger of (serious) injury from cuts.

- The bands can split and cause (serious) cuts when bent excessively.

No more safety precautions are necessary in the delivered form. The appropriate industrial and environmental safety measures must be taken for processing steps which cause dust (see also section 8): Prevent formation of dust. Ensure good ventilation/exhaustion at the workplace. Take note of emission threshold.

• Information about protection against explosions and fires: No special measures required.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Storage class: Not applicable
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:
 - Suction and filtering and good ventilation of the working area must be provided for processes where dust is formed.

Approved industrial vacuum cleaners of at least dust class M must be used (DIN EN 60335-2-69). Recommended: dust class H

Suitable breathing apparatus must be used during repair and maintenance work on suction systems (see personal safety equipment).

Control parameters

Components	 Components with limit values that require monitoring at the workplace: 		
7440-48-4 co	balt		
EL (Canada)	0.02 mg/m ³		
	IARC 2B		
EV (Canada)	0.1 mg/m ³		
PEL (USA)	0.1* mg/m ³		
	as Co; *for metal dust & fume, as Co		
REL (USA)	0.05* mg/m ³		
	inorg. compds.: *metal dust & fume, as Co		
TLV (USA)	0.02 mg/m ³		
. ,	as Co; BEI		
	(Con	td. on page 4)	

USA ·



Material Safety Data Sheet acc. to ISO/DIS 11014

Reviewed on 10/11/2011

Printing date 10/11/2011

Trade name: VITROVAC ®

	(Contd. of page 3
7440-21-3 sili	con
EL (Canada)	10 mg/m ³
EV (Canada)	10 mg/m ³
	total dust
PEL (USA)	15* 5** mg/m ³
	*total dust **respirable fraction
· · · ·	10* 5** mg/m ³
	*total dust **respirable fraction
TLV (USA)	TLV withdrawn
7439-89-6 iro	n
EV (Canada)	1* 5** mg/m³
	as iron;*salts, water-soluble;**welding fume
7439-98-7 mo	lybdenum
EL (Canada)	3* 10** mg/m ³
	as Mo; *respirable **inhalable
EV (Canada)	10* 3** 0.5*** mg/m ³
	metal,insol.compd.:*inh;**resp;sol.compd.:***resp
PEL (USA)	5* 15** mg/m ³
	as Mo;*soluble compds.,**insol.compds.:total dust
TLV (USA)	10* 3** 0.5*** mg/m ³
	insoluble compds.:*I,**R;***soluble compds.: R

• Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

• Breathing equipment:



In the case of dust formation (limit value exceeded), breathing apparatus must be worn. Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P2 or P3, for example:

- Full face mask (EN 136)
- Breathing mask (EN 149) FFP2 or FFP3
- 10 times the limit value (FFP2)
- 30 times the limit value (FFP3)
- Recommendation: P3

• Protection of hands:



Avoid repeated and prolonged contact with the skin, use protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

• Material of gloves

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

- Penetration time of glove material -
- Eye protection:



In the event of larger quantities of dust: Wear protective glasses / EN 166, poss. with side protection.

· Limitation and supervision of exposure into the environment The legal issue values and limitations are to be paid attention!

(Contd. on page 5)

USA

VACUUMSCHMELZE

Material Safety Data Sheet

acc. to ISO/DIS 11014

Reviewed on 10/11/2011

Trade name: VITROVAC ®

Printing date 10/11/2011

(Contd. of page 4)

• Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Strip	
Color:	Metallic	
• Odor:	Odourless	
• pH-value:	Not applicable.	
Change in condition Melting point/Melting range (app	vrox): 1000-1200°C	
Auto igniting:	Not applicable	
Danger of explosion:	Not applicable	
• Vapor pressure:	Not determined.	
• Density (approx) at 20°C:	7.8 g/cm ³	
Relative density	Not determined.	
 Solubility in / Miscibility with 		
Water:	Insoluble.	
 Other information 	No further relevant information available.	

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
 Possibility of hazardous reactions
- Hydrogen is released in contact with acid which can cause explosive gas mixtures.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values:

The following applies for the pure substance (here cobalt):

7440-48-4 cobalt

- Oral LD50 6170 mg/kg (rat)
- Primary irritant effect:
- on the skin: see sensitization
- on the eye:

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

Sensitization:

In the case of repeated and prolonged contact with the skin with metallic cobalt there is a possibility of sensitization.

Cobalt in the form of inhalable dust can lead to hypersensitisation when inhaled.

• Subacute to chronic toxicity:

In Germany, cobalt in the form of inhalable dust is classified as category 3 carcinogenic.

(Contd. on page 6)



acc. to ISO/DIS 11014

Reviewed on 10/11/2011

Trade name: VITROVAC [®]

Printing date 10/11/2011

(Contd. of page 5)

• Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

12 Ecological information

- Toxicity
- Acquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation: Observe offical regulations.
- Uncleaned packagings: Not applicable

14 Transport information

- Transport/Additional information:
- Land transport DOT / TDG

• Remarks: Non-hazardous goods from the standpoint of the specified regulations

- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Air transport ICAO-TI and IATA-DGR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture • Sara
- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):
- 7440-48-4 cobalt
- TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- Chemicals known to cause cancer:
- 7440-48-4 cobalt
- Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:
- None of the ingredients is listed.

(Contd. on page 7)

JSA



acc. to ISO/DIS 11014

Reviewed on 10/11/2011

Printing date 10/11/2011

Trade name: VITROVAC [®]

	(Contd. of page 6
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Cancerogenity categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
IARC (International Agency for Research on Cancer)	
7440-48-4 cobalt	2B, 2A
NTP (National Toxicology Program)	
None of the ingredients is listed.	
• TLV (Threshold Limit Value established by ACGIH)	
7440-48-4 cobalt	A3
7439-98-7 molybdenum	A3
MAK (German Maximum Workplace Concentration)	
7440-48-4 cobalt	2
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
National regulations:	
 Other regulations, limitations and prohibitive regulations 	
e.g.	
- guidelines 67/548/ECC, 1999/45/EC - 1272/2008/EG (CLP)	

- 1272/2008/EG (CLP)
- 1907/2006/EG (REACH)
- German Hazardous Substances
- Chemical safety assessment: Void (for articles)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

- H228 Flammable solid.
- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H413 May cause long lasting harmful effects to aquatic life.
- R11 Highly flammable.

R42/43 May cause sensitization by inhalation and skin contact.

R53 May cause long-term adverse effects in the aquatic environment.

• Department issuing MSDS:

Department HT-F Tel. 06181/38-2045

• Contact:

Environmental Protection Department Tel. 06181/38-2359

• Abbreviations and acronyms: ACGIH: American Conference of Governmental Industrial Hygienists LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

- Sources
- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe
- BIA-Gefahrstoffdatenbank